




# BEARING ITALIA S.P.A



skf FSAF 1515 x 2.1/2 T SAF and SAW pillow blocks with bearings on an adapter sleeve

Bearing No. FSAF 1515 x 2.1/2 T

FSAF 1515 x 2.1/2 T Bearing 2D drawings and 3D CAD models

$d_a$	63.5 mm
$D_a$	130 mm
$C_a$	37.008 mm
$A_1$	79.375 mm
$A_2$	193.675 mm
$b_a$	30.163 mm
H	157.559 mm
$H_1$	82.55 mm
$H_2$	28.575 mm
J min.	219.075 mm
J max.	244.475 mm
$J_1$	47.625 mm
L	285.75 mm
$N_1$	15.875 mm
$R_1$	46.038 mm
$R_2$	21.431 mm
$R_G$	1/4 NPT
$P_G$	1/8 NPT
h	31.75 mm
Housing	FSAF 515
Bearing	1215 K
Adapter sleeve assembly	SNW 15x2.1/2
Stabilizing ring	2 x SR-15-0
Taconite seal	TER 38
End plug (suffix Y)	EPR 7



## BEARING ITALIA S.P.A

Max. speed for Taconite seal	1250 r/min
P <sub>60°</sub>	54.3 kN
P <sub>90°</sub>	32.5 kN
P <sub>120°</sub>	20 kN
P <sub>150°</sub>	18.2 kN
P <sub>180°</sub>	22.2 kN
P <sub>a</sub>	5.65 kN
Mass pillow block	12.7 kg
Cap bolt	2 x 1/2-13 UNC
Cap bolt recommended tightening torque	81.3 N · m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.5 in
Initial grease fill	136.08 g