




BEARING ITALIA S.P.A



skf SSAFS 22217 SAF and SAW pillow blocks
with bearings with a cylindrical bore

Bearing No. SSAFS 22217

SSAFS 22217 Bearing 2D drawings and 3D CAD models

d_a	85 mm
d_b	100.013 mm
d_c	80.963 mm
D_a	150 mm
C_a	45.796 mm
A_1	88.9 mm
A_2	127 mm
S	4.763 mm
b_a	35.719 mm
H	187.325 mm
H_1	95.25 mm
H_2	38.1 mm
L	330.2 mm
R_1	53.975 mm
R_2	22.225 mm
R_G	3/8 NPT
P_G	1/8 NPT
h	34.925 mm
Housing	SAFS 217
Bearing	22217 E
Lock nut	AN 17
Lock washer	W 17
Stabilizing ring	SR-17-14
Labyrinth ring (d_b shaft position)	LOR 89
Labyrinth ring (d_c shaft position)	LOR 63



BEARING ITALIA S.P.A

position)	
End plug (suffix Y)	EPR 9
Bearing limiting speed	5600 r/min
P_{60°	78.7 kN
P_{90°	47.2 kN
P_{120°	28.9 kN
P_{150°	26.7 kN
P_{180°	32 kN
P_a	20.5 kN
Mass pillow block	23.6 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N · m
Cap bolt, SAE grade	8
Initial grease fill	218.29 g