




# BEARING ITALIA S.P.A



skf 351006 A Single direction thrust ball bearings

Bearing No. 351006 A

351006 A Bearing 2D drawings and 3D CAD models

Size	1500x1250x150 mm
Bore Diameter	1500 mm
Outer Diameter	1250 mm
Width	150 mm
d	1250 mm
D	1500 mm
H	150 mm
d <sub>1</sub>	1492 mm
D <sub>1</sub>	1258 mm
r <sub>1,2</sub> - min.	6 mm
d <sub>a</sub> - min.	1392 mm
D <sub>a</sub> - max.	1358 mm
r <sub>a</sub> - max.	5 mm
Basic dynamic load rating - C	1430 kN
Basic static load rating - C <sub>0</sub>	16000 kN
Fatigue load limit - P <sub>u</sub>	160 kN
Reference speed	220 r/min
Limiting speed	300 r/min
Minimum load factor - A	1300
d <sub>1</sub>	1492 mm
D <sub>1</sub>	1258 mm
r <sub>1,2</sub> min.	6 mm
d <sub>a</sub> min.	1392 mm
D <sub>a</sub> max.	1358 mm
r <sub>a</sub> max.	5 mm



## BEARING ITALIA S.P.A

Basic dynamic load rating C	1430 kN
Basic static load rating $C_0$	16000 kN
Fatigue load limit $P_u$	160 kN
Minimum load factor A	1300
Mass bearing (including seat washer where applicable)	515 kg